

TRX 5800



TRX: MADE TO MEASURE

TRX5800 is a multi-purpose specialised tractor ideal for open field or row crop applications, in orchards and vineyards, on level ground or slopes. The TRX is an isodiametric, made-to-measure specialised tractor, offering outstanding manoeuvrability with a tight turning radius.

Thanks to the sparkling performance of the engine and constant grip ensured by the overhung engine and four-wheel drive, the TRX is stable in all situations.

The TRX's extraordinary versatility is a result of the reversible driving position: this feature enables a whole new approach to working procedures, allowing the use of a wide range of implements for ploughing, spraying, harvesting, towing, green keeping, forestry and construction site work. The reversible driving position and ergonomic control layout simplify the task of the operator, thereby reducing fatigue and stress.

TRX 5800



Chassis: "ACTIO™" – Full chassis with oscillation

- Reversibility RGST™ • Steering wheels • 4 equal wheel drive
- Rear final drive

Engine: Diesel indirect injection with counter rotating weight system - Stage 3A - 4 Cylinders - Power 36,5 kW / 49,7 HP 3000 rpm 2190 CC - Torque max (Nm/revs) 139/1750

Transmission: Synchronized 32 speed gear box: 16 forward and 16 reverse with synchronized inverter

PTO: Rear, independent and synchronized at 540/540E rpm with progressive electrohydraulic engagement

Rear hydraulic lift: with 3 point hitch
Operating Pressure 160 bar - Capacity 2100 Kg

Brakes: Standard: hydraulic front and rear disk brakes in oil bath, rear steering brakes - Independent emergency and parking brake: band type on transmission

Weight in order of speed:

With roll bar 1735÷1825 Kg - With cab: 1910÷2000 Kg

Standard equipment

- RGST™ Reversible driving position • Differential locking on rear axle only or both axles with electro-hydraulic control • Lift arms with Cat. 1-2 fixed ball ends • Sprung adjustable seat with safety belt • Folding front roll bar with easy operation • Adjustable wheel discs • Rear auxiliary hydraulic system with 3 control levers • Height-adjustable rear tow hook • Multifunction digital console • Accelerator pedal suspend on turret • Battery • Battery disconnecter • Electrical outlet socket • Safe start system on shuttle control, on PTO and on seat

Optional

- Cab with air conditioning and roof hatch on Silent Block mountings
- Lift and hydraulic quick couplers controlled by double speed "ON/OFF" Joystick • Power lift with draft and position control and 3-point linkage • Rear power lift with suspension • Hydraulic third hitch and vertical tie-rod



DIMENSIONS: tyres 280/70-18

