



# HR



Tractor people







Groundcare

## **HR: Hydrostatic, Reversible.**

HR, the new 57 hp Antonio Carraro reversible hydrostatic tractor, offers exceptional performance along with great versatility of use.







The **hydrostatic transmission** grants unbeatable operative practicality during rapid forward and backward movements in quick succession. The reverser lever allows to change quickly and easily the drive direction. It is fitted with the **speed-fix** device, an authentic specialist when executing activities that require constant forward speeds.

The **RGS™** system allows to change the drive direction in a short time thus multiplying the operative possibilities whilst remaining perfectly ergonomic.


On request the HR 6500 can be fitted with electrohydraulic **ON/OFF Joystick** with 2 speeds. This optional extra further enhances the unique performance and operational comfort.

The lifting system with **new geometry** has independent lift cylinders. The tractor's configuration with **larger rear wheels** guarantees constant ground grip and grants decisive, contained turning.

At the buyer's discretion the HR 6500 can be fitted with a protection bar (standard) or the **"Star Light"** cab with heating, soundproofing and air conditioning system (optional).







# HR

www.antonio carraro.com



## HR 6500

<b>Chassis</b>	ACTIO™ – Full chassis with oscillation • Steering wheels • Reversibility RGS™ • 4 unequal wheel drive		
<b>Engine Type</b>	Diesel indirect injection with counter rotating weight system Laws regarding emissions: Stage 3A    N° Cylinders: 4 Turbo Displacement (CC): 2216    Power kW/HP (97/68/CE): 41,5/57 Maximum engine revs: 2600    Torque max (Nm/revs): 185/1800 Cooling: Water    Tank Capacity (litres/gal): 50/13		
<b>Transmission</b>	Hydrostatic – Continual variation of forward speeds in both drive direction from 0>30 Km/h with a mechanical selector of the 4 speed variator - Speed control with "Speed-fix"		
<b>PTO</b>	Rear, independent and synchronised at 540/540E rpm with progressive electrohydraulic engagement		
<b>Shaft</b>	Profile 1" 3/8 with 6 splines with facilitated engagement		
<b>Transmission clutch</b>	Hydraulic control		
<b>Drive disengagement</b>	Electro-hydraulic control on the front		
<b>Hydraulic Lift</b>	With 3 point hitch and adjustable lowering speed control		
<b>Capacity (Kg/lbs):</b>	2100/4630		
<b>Operating Pressure (bar)</b>	160		
<b>Steering</b>	Hydraulic with 2 pistons with "Load sensing"		
<b>Brakes</b>	Standard: Hydraulic front and rear disk brakes in oil bath - Independent rear steering brakes - Emergency and parking: band type on transmission		
<b>Platform</b>	Suspended on Silent Block		
<b>Tyres Front</b>	260/70 R16	31x15.50-15	29x12.50-15 Garden
<b>Rear</b>	300/70 R20	450x55-17	36x13.50-15 Garden
<b>Minimum external width (mm/in)</b>	1400/55.1	1670/65.7	1565/61.6
<b>Ground clearance (mm/in)</b>	245/9.65	235/9.25	230/9.06
<b>Weight in order of speed:</b>			
<b>With roll bar (Kg/lbs)</b>	1990/4387		
<b>With cab (Kg/lbs)</b>	2240/4938		
<b>Standard Features</b>	Reversible control tower • Rear or front/rear differential locks with electrohydraulic control • Hydraulic system with 2 separate hydraulic pumps • Adjustable steering wheel • Lifting bar with quick release couplings • Adjustable, suspension seat • Safety Belts • Foldable safety frame • Rear hydraulic system with 2 levers • Rear adjustable height tow hitch • Front tow hitch • Multifunctional dashboard with digital ground speed and PTO rpm indication "Star Light" cab with heating, soundproofing and air conditioning system • Lifting and hydraulic outlets controlled by electrohydraulic ON/OFF Joystick with 2 speeds • Power lift with position and draft control • Adjustable lifting bar with quick release couplings • Power lift with hydraulic 3rd point and vertical adjusting links • Rear PTO 540/1000 rpm • Pneumatic suspension seat • Slider trailer hook • Cast iron wheel centre for 20" rear wheels		
<b>Optional Features</b>			

The description and illustrations in this brochure are provided simply for information purposes; they are not binding and may be varied at any time without notice.

Antonio Carraro spa  
 Via Caltana, 24  
 35011 Campodarsego Padova  
 Tel +39 049 9219921  
 Fax +39 049 9219944  
 E-mail info@antonio carraro.it

Cod. 4 7318 124 - 04/2010

